



1975 Scirocco

1975 Scirocco

Scirocco.
 Styled by Giugiaro of Italy. To be contemporary.
 Engineered by Volkswagen. To take performance seriously.

- 1—4 cylinder, water-cooled, overhead cam, transverse mounted engine. Up front.
- 2—Front wheel drive.
- 3—Front disc brakes, power assisted.
- 4—4-speed, fully synchronized, transverse mounted transmission. Or optional 3-speed automatic.
- 5—4-wheel, independent suspension.
- 6—Negative steering roll radius.
- 7—Independent, rear stabilizer axle.
- 8—Lightweight, aluminum-magnesium alloy rims.
- 9—Rack and pinion steering.
- 10—Steel belted radial tires.

Scirocco.
 A commitment to the future. When it's needed most.
 Now. From Volkswagen.

SPECIFICATIONS		VW SCIROCCO	
ENGINE:	Type	Water-cooled, transverse-front mount, overhead cam	
	No. cylinders	4 cyl. in-line	
	Bore	76.5 mm. (3.01 in.)	
	Stroke	80.0 mm. (3.15 in.)	
	Displacement	1471 cc. (89.75 cu. in.)	
	SAE Net H.P.	70/6000 rpm.	
	Max. Torque, SAE Net	81/3500 rpm.	
	Compression Ratio	8.2:1	
	Carburetion	Two-stage downdraft carburetor, automatic choke.	
	TRANSMISSION & DIFFERENTIAL:	Type	Fully synchronized, transverse front mounted.
No. Speeds		4 forward, 1 reverse.	
Final drive		Front wheel drive, double jointed axles.	
Clutch		Single disc, dry.	
CHASSIS & SUSPENSION:	Frame	Unitized body with energy absorbing front and rear sections. Bolt-on front fenders.	
	Suspension-Front	Independent, coil/shock absorber struts with lower triangular control arms. Negative steering roll radius.	
	Suspension-Rear	Coil/shock absorber struts. Independent stabilizer axle.	
	Service Brake	Dual diagonal, power assisted. Discs front w/single piston floating caliper.	
	Parking Brake	Cable operated, rear.	
	Rim Size	5J x 13	
	Tire Size	Radial ply, steel belted, 175/70 SR 13	
	Steering	Rack and pinion	
	ELECTRICAL SYSTEM:	Rated Voltage	12V/55 A. Alternator
		Battery	12V 54 AMP/h
Ignition		Battery, coil, distributor	
DIMENSIONS:		Wheelbase	94.5 in.
	Track, front	54.7 in.	
	Track, rear	53.1 in.	
	Length	155.7 in.	
	Width	64.0 in.	
	Height	51.5 in.	
	Ground Clearance	5.3 in.	
	Turning Circle	32.2 ft. (approx.)	
	WEIGHTS:	Dry Weight	1874 lbs.
		(automatic)	1929 lbs.
Payload		838 lbs.	
(automatic)		783 lbs.	
PERFORMANCE:	Top Speed	104 mph.	
	(automatic)	101 mph.	
	Fuel Consumption DIN 70030	29 mpg.	
	(automatic)	27 mpg.	
	Acceleration	0-60 10.3 sec.	
	(automatic)	0-60 11.8 sec.	